



Professional Packaging Systems

2010 S. Great Southwest Parkway
Grand Prairie, Texas 75051
www.ProPac.com

Contact

Our Packaging Experts
solutions@propac.com
888-318-0083

Matrix INVpack PH6 & PH9 Multi-Lane Stickpack Machines



At a Glance

- Produces three-side-seal stickpacks for the pharmaceutical industry
- Closed main frame, servo motor drive
- Complies with GMP regulations, designed and built under the strictest manufacturing standards
- 6 to 15 lanes

Buy your [vffs film](#) from us, and get a discount on this Matrix machine!

Pricing

Call us at 888-318-0083

Many options are available. Complete details will need to be finalized to determine requirements and final system costs. Work with your Pro Pac representative to build this machine to your specifications.

Produces Three-Side-Seal Stickpacks for the Pharmaceutical Industry

The Matrix INVpack PH6 and PH9 stickpack machines produce three-side-seal stickpacks for powders, granulates, liquids, pasty, and solid products for the pharmaceutical industry.

The PH6 and PH9 machines feature a closed main frame and are driven by servo motors engines. The reel is enclosed inside the cabinet to dust from entry. These machines are manufactured according to the most demanding rules in order to comply with the most strict norms and rules.

The INVpack machines for the pharma sector comply with GMP regulations and are designed and built under the strictest manufacturing standards. INVpack can supply DQ, IQ and OQ documentation, as well as the functional analysis of the machine or other type of documentation that may be required. Our service technicians can assist during the execution of the IQ and OQ.

Features & Benefits

Small footprint

Machines comply with GMP regulations

Available with a variety of lanes choices for flexibility

Powerful horizontal sealer

Touch screen panel

PLC control

Can package liquid, pasty, granulated, powder or solid products

PH6 Specifications

	6 Lanes	7 Lanes	8 Lanes	10 Lanes	12 Lanes	15 Lanes
CPM	420	490	560	700	840	1050
Packet Width (mm)	17 - 45	17 - 37	17 - 30	17 - 25	17 - 20	17 - 17
Packet Length (mm)	60 - 200					
Max Film Width (mm)	600					
Max Roll OD (mm)	600					
Roll Core OD (mm)	70 / 150					
Machine Weight (kg)	2500					
Noise (db)	<70					
Electrical	220, 400, 440, Vac / 3Ph+N+PE / 50,60Hz					
Air Pressure	6 bar					

PH9 Specifications

	8 Lanes	10 Lanes	12 Lanes	15 Lanes	18 Lanes
CPM	560	700	840	1050	1260
Packet Width (mm)	20 - 45	20 - 40	20 - 32	20 - 25	20 - 20
Packet Length (mm)	60 - 200				
Max Film Width (mm)	900				
Max Roll OD (mm)	600				
Roll Core OD (mm)	70 / 150				
Machine Weight (kg)	2600				
Noise (db)	<70				
Electrical	220, 400, 440, Vac / 3Ph+N+PE / 50,60Hz				
Air Pressure	6 bar				

Please [contact Pro Pac](#) or call 888-318-0083 for your vertical form fill seal bagging equipment.